

RESPONSE UNDER 37 C.F.R. § 1.116**EXPEDITED PROCEDURE – Art Unit 1742**

Attorney Docket No. 29195-8181US3

SEMITOOL REF NO. P96-0010US4

Amendments to the Claims:

Following is a complete listing of the claims pending in the application, as amended:

1 - 7. (Cancelled)

8. (Currently Amended) A workpiece processing method comprising:
positioning an electrode against a workpiece surface, said electrode having an
electrode tip having a sheath, said sheath having a sheath tip rim;
engaging said workpiece surface with said sheath tip rim to thereby cause the
sheath tip rim to splay outwardly upon said contacting to form a
continuous seal about the periphery of said electrode tip; ~~and~~
with said electrode tip electrically engaging said workpiece, imparting a desired
electrical bias to said workpiece; and
electrochemically processing the workpiece.

9. (Previously Presented) The workpiece processing method of claim 8
further comprising supporting said workpiece in a position adjacent said sheathed
electrode.

10. (Previously Presented) The workpiece processing method of claim 8
wherein said positioning step comprises:

moving said electrode along a first motion axis away from a disengaged position;
and
moving said electrode along a second motion axis that is different from said first
motion axis toward an engaged position.

RESPONSE UNDER 37 C.F.R. § 1.116**EXPEDITED PROCEDURE – Art Unit 1742**

Attorney Docket N . 29195-8181US3

SEMITOOL REF No. P96-0010US4

11. (Previously Presented) The workpiece processing method of claim 8 wherein said positioning step comprises:

longitudinally moving said electrode along a longitudinal movement axis away from a disengaged position in which said workpiece surface is not engaged by said electrode tip; and
rotating said electrode about said longitudinal movement axis toward an engaged position in which said electrode tip is placed in electrical contact with said workpiece surface.

12. (Previously Presented) The workpiece processing method of claim 8 wherein said positioning step comprises:

moving said electrode along a first motion axis away from a disengaged position;
moving said electrode along a second motion axis toward an engaged position, said second motion axis being different from said first motion axis;
said engaging step comprising advancing said electrode tip from a retracted position within the sheath to an unretracted position in which said workpiece surface is physically engaged by the electrode tip.

13. (Previously Presented) The workpiece processing method of claim 8 wherein said positioning step comprises:

longitudinally moving said sheathed electrode along a longitudinal movement axis away from a disengaged position in which said workpiece surface is not engaged by said electrode tip;
rotating said electrode about said longitudinal movement axis and toward an engaged position in which said electrode tip may engage said workpiece surface; and
said engaging step comprising advancing said electrode tip from a retracted position within the sheath to an unretracted position in which said workpiece surface is physically engaged by the electrode tip.

RESPONSE UNDER 37 C.F.R. § 1.116**EXPEDITED PROCEDURE – Art Unit 1742**

Attorney Docket No. 29195-8181US3

SEMITOOL REF No. P96-0010US4

14. (Previously Presented) A process for electroplating a metal onto the surface of a workpiece comprising:

placing the workpiece upon a processing head including an electrode contact assembly, the electrode contact assembly comprising at least one electrode contact having a contact tip and at least one sealing member disposed proximate the contact tip of the at least one electrode contact, the at least one sealing member including a resilient rim;

driving the electrode contact assembly into engagement with the workpiece to place the at least one electrode contact into electrical engagement with the workpiece, the at least one sealing rim splaying away from the contact tip of the at least one electrode contact to thereby form a continuous seal against a surface of the workpiece;

placing the workpiece into contact with an electrolyte;

providing electrical power to the at least one contact and an anode disposed in electrical contact with the electrolyte to thereby electroplate the metal on the workpiece.

15. (Previously Presented) A process for electroplating a metal onto the surface of a workpiece comprising:

placing the workpiece upon a processing head including an electrode contact assembly, the electrode contact assembly comprising a plurality of electrode contacts each having a contact tip and a plurality of sealing members respectively associated with an proximate each of the contact tips, each of the plurality of sealing members including a respective resilient rim;

driving the electrode contact assembly into engagement with the workpiece to place the plurality of electrode contacts into electrical engagement with the workpiece, the sealing rims splaying radially outward from each respective

RESPONSE UNDER 37 C.F.R. § 1.116**EXPEDITED PROCEDURE – Art Unit 1742**

Attorney Docket No. 29195-8181US3

SEMITOOL REF No. P96-0010US4

contact tip to thereby form a continuous seal against a surface of the
workpiece around the respective contact tip;
placing the workpiece into contact with an electrolyte;
providing electrical power to the plurality of electrode contacts and an anode
disposed in electrical contact with the electrolyte to thereby electroplate
the metal on the workpiece.

16-26. (Cancelled)

27. (New) A workpiece processing method comprising:

positioning an electrode against a workpiece surface, said electrode having an
electrode tip having a sheath, said sheath having a sheath tip rim;
engaging said workpiece surface with said sheath tip rim to thereby cause the
sheath tip rim to splay outwardly upon said contacting to form a
continuous seal about the periphery of said electrode tip;
with said electrode tip electrically engaging said workpiece, imparting a desired
electrical bias to said workpiece; and
exposing the electrically biased workpiece to an electrolyte, the continuous seal
separating a contact of the electrode from the electrolyte.